




Control and Automation in Solar-Powered Homes



Joshua de la Rosa, Department of Electrical Engineering, Arizona State University, Tempe, AZ
Prof. Bruce Land, Department of Electrical and Computer Engineering, Cornell University, Ithaca, NY
2009 Cornell University Solar Decathlon


- About Cornell Solar Decathlon (CUSD)
 - Undergraduate students (all backgrounds/majors)
 - Build completely solar-powered house
 - Competes with other schools
- About the Engineering Team
 - Design control system for house (lighting, HVAC)
 - Early Start = No House (no HVAC) = Big Challenge!



The Bigger Picture

- Floor Specifications
 - 460 sq. ft.
 - Three Cylindrical Silos
 - 1 Bedroom
 - 1 Bath
 - 1 Living Room
 - Kitchen w/ Island
 - 15' x 15' Courtyard
 - Meant for 1-2 residents
- Design Specifications
 - PV Panels on Roof
 - Mechanical Closet
 - Corrugated Steel Wall





Background



- The Goal to reach by end of Summer:
 - Design & Build bench-top model to simulate control system
 - Develop easy-to-follow protocol for installation
- Donated Equipment
 - ELK Products
 - Smart Homes Insteon



I N S T E  N






Hardware Methodology


“Putting It Together”



Implementing Hardware

- Control Box
 - Ethernet Interface
 - Serial Interface
 - Control Board
- Two Controllers
 - Keypad
 - Computer Software
- Powerline Network Device





Hardware Methodology

“Putting It Together”

- Three Configurations (but anything controls anything)

- A controls B

- Not Hardwired

- Network-Linked

- C controls D


- Regular outlet

- Hardwired


- E controls F

- Regular bulb

- Hardwired



a) b) c) d) e) f)




Engineering Design

“How It Works”



ARIZONA STATE
UNIVERSITY

- User's Perspective
 - Centralized Control
 - Remote Control (Virtual & Real Keypad)
 - GUI Software = Easy-to-Use Interface







Engineering Design

“How It Works”

- Engineer’s Perspective
 - Add carrier frequency (131.65 kHz) to powerline voltage.
 - Data is modulated on carrier frequency using Binary Phase-Shift Keying (BPSK).
 - 10 cycles per bit






Engineering Design


“How It Works”

- Engineer's Perspective

- Peer-to-Peer Networking

- Controller (sends data)
 - Responder (receives data)
 - Repeater (relays data)






Results

“Did It Work?”


- Initial Malfunctions/Discrepancies
 - Main Control Board
 - Bad Powerlinc Modem
 - Broken SwitchLinc Dimmer
- Debugging the Control Board/Modem
 - Able to connect (ping)
 - Not able to communicate
- Cooperative Vendors




Results

“Did It Work?”


- Manual Test
 - Testing switches to turn on corresponding outlets/bulb
- Remote Access Test
 - Being able to turn on/off switches through keypad and rules we wrote
- Simple Automation Test
 - Program to toggle switches/outlets every two minutes
- Interoperability Automation Test
 - Takes temperature readings
 - If it gets warm, control turns on fan and shuts off lights






Acknowledgements

- This research was supported by the Cornell University Louis Stokes Alliance for Minority Participation (CU-LSAMP).


Dr. Scamman
Cornell University
College of Engineering



INSTEON



- Major equipment provided by ELK Products and INSTEON.
- Funding and participation provided by Cornell University Solar Decathlon (CUSD) Faculty Advisors.